

LCD & TFT MONITORS

Specifications

LCD & TFT MONITORS	
Visible screen size (cm) / Size	47 / 18.5"
Screen format	16:9
Display area (mm)	410 x 230
Response Time	5 ms
Maximum Resolution	1366 x 768@60Hz
Analogue Input: D-Sub	x
D-Sub 15 pin	x
Power Source	110~240VAC, 50/60Hz
Power Consumption	on ← 25W, standby:← 1W



MON-17LCD-AR

Features

- Professional TFT LCD for CCTV
- VGA(640X480), SVGA (800X600), XGA(1024X768), SXGA(1280X1024)
- BNC Video inputs support NTSC / PAL standards
- Picture-In-Picture feature that allow multi-picture display
- Built-in 3D comb filter and 3D de-interlace for crispy picture performance
- Provides Key Lock function for easy management
- Video looping output supports 75ohm auto termination
- Support audio and live-out function with stereo phone jack output



191A

Features

- Superior stainless steel construction.
- IP65 and NEMA certified
- HD Ready with HDMI & 720p/1080i and component inputs.
- Direct heated screen technology avoids misting fast.
- Superior widescreen high contrast/response LCD screen with dynamic contrast enhancement. (800:1 + 500 cd/m, 5ms).
- Fast easy one fit installation and compact design.



TFT-3.5TM

Features

Professional 3.5" Test Monitor with 6 essential CCTV tools built into one.

- 3.5" Video Test Monitor
- Built in RS-485 PTZ Control
- Video Signal Strength plus pattern generator
- Cable Current
- DC/AC Voltage Tester
- Built in speaker
- Up to 5 hours batter life

